



AFH Presents

NMI approved Turbine flowmeters

The Satam turbine meter Model ZT



SATAM

Sectors of application

- **Oil depots**
tank-trucks, rail cars and ships.
- **Aircrafts refueling**
refuelers and oil dispensers.
- **Liquid hydrocarbons**
transportation by pipeline, Metering of light fuels
- **Marine**
Filling of fuel tanks.
- **Refinery**
Custody metering, production processes.



Applications



Liquid :Accuracy = +/-0.15%
Repeatability: +/-0.02%

Turbines flow meters

Our Range of Turbines flow meters with

- Integrated Flow straighteners
- Dual Magnetic pick up coil
- ANSI 3 to 4 Inch body
- 316L Body and Aluminium Impeller

TLM 3 -30 500 LPM 3" Body

TLM 3 -50 833 LPM ANSI 150 3" Body

TLM 3 -70 1166 LPM ANSI 150 3" Body

TLM 3 -110 110 1833 LPM ANSI 150 3" Body

TLM 3 -150 2500 LPM ANSI 150 3" Body

TLM 4 -70 1166 LPM ANSI 150 4" Body

TLM 4 -110 1833 LPM ANSI 150 4" Body

TLM 4 -150 2500 LPM ANSI 150 4" Body

TLM 4 -200 3333 LPM ANSI 150 4" Body

TLM 4 -300 5000 LPM ANSI 150 4" Body Stainless



Head Office 1, 25-27 Burns Road, Altona, Victoria 3018,
Phone 03 9369 6200, Fax 03 9369 6233, Email: support@afhpl.com.au
www.afhpl.com.au